

panelform™

StyleLite® ACRYLIC
DOORS & PANELS



ZeroLine
GLUELESS EDGING TECHNOLOGY

Panelform StyleLite doors are a very popular choice for perfect gloss and silky smooth velvet finishes.

Created in 18mm acrylic-faced MDF board, StyleLite acrylic doors and panels offer a sophisticated, yet practical finish.

Choose StyleLite to lift the atmosphere and enhance the sense of space in your home, whilst keeping surfaces both easy-care and durable.

ZeroLine technology available.

StyleLite ZeroLine Doors

ZeroLine is the newest technology to come to kitchen door manufacturing. StyleLite doors are 18mm thick with a 1mm 'laser edge' tape.

ZeroLine technology enables the 1mm edge tape to be 'fused' to the edge of the door or panel without using glue, creating an almost invisible join that is exceptionally strong and highly water resistant.

ZeroLine uses specially manufactured ABS or PP edge tapes which are more environmentally friendly than traditional PVC tapes.

Visit panelform.co.nz to learn more about ZeroLine Glueless Edging Technology.



Colours

The swatches below are the colours available in the StyleLite colour selection. These colours may change periodically as market trends dictate. Please check availability prior to ordering.

Please note the colours shown may vary slightly from actual colours due to the printing process of this brochure, so always select a colour based on an actual sample swatch.



Care & Maintenance

StyleLite doors are made from 18mm acrylic-faced E0 MR MDF board. Care should be taken to ensure the door edges are not exposed to high levels of heat, moisture or steam, and that any accidental spills are wiped up immediately.

The StyleLite surface becomes more scratch resistant over the first few days after the removal of the protective film. This process can be accelerated by lightly polishing the StyleLite surface immediately after the film is removed using Novus No. 1 or Plexus plastic polishes with a clean microfibre cloth.

Please Note: The advice below applies only to StyleLite high gloss products.

General cleaning: Apply Novus No. 1 Plastic Polish, Plexus Plastic Polish or warm soapy water and wipe using a clean microfibre, soft cloth or damp chamois.

Removing marks and light scratches: Apply Novus No. 2 or a good quality liquid polish and using a damp, clean microfibre or soft cloth, polish in a circular pattern. Then remove polish using the general cleaning procedure above.

Removing heavier scratches: Apply Novus No. 3 or a good quality fine compound polish and using a damp, clean microfibre or soft cloth, polish in back and forth motion at right angles to visible scratches. Follow with the removing marks and light scratches and general cleaning procedure above.

Ensure all polish residues are removed completely from the StyleLite surface. Low speed electric buffing can also be used to repair marks and scratches.

Do not:

- Use a paper towel to clean.
- Dry wipe doors and panels at any time.
- Use brushes, scourers or scrapers on doors and panels.
- Use abrasive cleaners, thinners or methylated spirits.

Doing any of these will void your 10 year warranty.

Installation

StyleLite acrylic doors and panels are manufactured with a protective film on the surface to prevent scratching. This film should not be removed until installation is complete.

10 Year Guarantee

Panelform guarantees StyleLite doors and panels will stand the test of time. As manufacturers we have full confidence in our design and workmanship and will guarantee this in all our products for 10 years, subject to some terms and conditions.

This guarantee is in addition to the guarantees as contained in the Consumer Guarantees Act 1993 and does not in any way limit the rights which may be available to the consumers under that Act.

For full guarantee terms and conditions, please visit panelform.co.nz

panelform™

StyleLite® ACRYLIC
DOORS & PANELS



ZeroLine
GLUELESS EDGING TECHNOLOGY

Phone: 03 982 1195
Fax: 03 982 1971
Email: info@panelform.co.nz
49 Vickers Road, Christchurch
panelform.co.nz